

All-round INDUCTION - 28kw - Top version

CODICE
CR1358529

MODELLO
D94/10TCIITC

SERIE
DIAMANTE 90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

■ Unbreakable glass-ceramic top. ■ Serigraphs identifying cooking zones. ■ Safety sensor to prevent overheating. ■ Power adjustable to 12 levels ■ Heating by means of an inductor equipped with a device that detects the presence of the cooking vessel on the cooking zone and automatically switches the heating on/off, and a device against overheating.

■ Ensures the correct positioning and suitability of the pot ■ Power adjustable to 12 levels ■ Professional components tested to withstand intensive use over time ■ Safety sensor to prevent overheating. ■ Cooking zones with 7KW power ■ Mechanically controlled induction ready for IOT connection to Cloud ■ Serigraphs identifying cooking zones.

All-round INDUCTION - 28kw - Top version

CODICE
CR1358529

MODELLO
D94/10TCIITC

SERIE
DIAMANTE 90

Technical Information

| SPECIFICATION | DATA |
|-----------------------|------------------------------------|
| MATERIAL | CR1358529 |
| DEFINITION | D94/10 TCIITC INDUZIONE M80 TC TOP |
| COMMERCIAL LINE | DIAMANTE |
| SUPPLY | ELECTRICS |
| DIM. WIDTH | 800 mm |
| DIM. PRODUCTIVITY | 900 mm |
| DIM. HEIGHT | 870 mm |
| NET WEIGHT | 63 Kg |
| VOLUME (net) | 0,626 |
| PACKAGE LENGTH | 850 mm |
| PACKAGE WIDTH | 1020 mm |
| PACKAGING HEIGHT | 1150 mm |
| PACKAGE VOLUME | 0,997 m3 |
| GROSS PACKING WEIGHT | 72.4 Kg |
| STANDARD POWER SUPPLY | 380-415V 3 |
| FREQUENCY | 50/60 Hz |
| ELECTRICAL POWER | 20,000 kW |
| IP GRADE | IPX5 |
| CERTIFIED MODEL | D94/10 TCIITC |

All-round INDUCTION - 28kw - Top version

CODICE
CR1358529

MODELLO
D94/10TCIITC

SERIE
DIAMANTE 90

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESHEMA - IINSTALLATIONSRTNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm
MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda

| | |
|--|---|
| E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico | G Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás |
| S Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água | H20 Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de agua - Wateraansluiting - Junção alimentação água |
| S1 Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba | A1 = Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno A2 = Fredda - Kalt - Cold - Froid - Fria - Koude - Frio |
| S2 Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de depresión - Onderdrukkelep - Válvula de depressão | |
| S3 Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de agua intersticios - Afvoer water tussenruimte - Descarga de água na marmitta com Sistema de aquecimento indirecto | |
| S4 Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno | L Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaakraan - Torneira de nível |

All-round INDUCTION - 28kw - Top version

CODICE
CR1358529

MODELLO
D94/10TCIITC

SERIE
DIAMANTE 90



Power adjustable to 12 levels



Mechanically controlled induction
ready for IOT connection to Cloud



Professional components tested to
withstand intensive use over time



Safety sensor to prevent overheating.



Cooking zones with 5KW power

All-round INDUCTION - 28kw - Top version

CODICE
CR1358529

MODELLO
D94/10TCIITC

SERIE
DIAMANTE 90

ACCESSORIES

| CODE | MODELLO | DESCRIZIONE |
|-----------|---------|--|
| CR1355469 | D94/10B | Open base 80cm series 90 |
| CR0996979 | DBVP4 | Diamond door 39.5x3.6x46.5 cm for 40 cm compartments |
| CR0997009 | DBVPA4 | Accessory Diamond door 39.5x3.6x46.5 cm for 40 cm compartments |
| CR0997029 | DAPC | Accessories for accessory diamond knife holder |
| CR0997019 | DAPD | Accessories for Diamond door accessories |
| CR0997039 | DAPS | Accessories for diamond spice rack |
| CR0997049 | DAPM | Accessories for accessory Diamond door |
| CR0997059 | DAPDB | Accessories for accessory Diamond door/bottle holders |
| CR1353589 | DBVC4 | Drawer kit 39.5x56x46.5 cm for compartments of 40 |