

NEUTRAL ELEMENT WITH OPEN COMPARTMENT

CODICE
CR0995019

MODELLO
D71/10EN

SERIE
DIAMANTE 70



GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200. Wide range of accessories.

TECHNICAL SPECIFICATIONS

■ Modular, easy to combine and robust. ■ Drawers for GN 1/1 ■ Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

NEUTRAL ELEMENT WITH OPEN COMPARTMENT

CODICE
CR0995019

MODELLO
D71/10EN

SERIE
DIAMANTE 70

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0995019
DEFINITION	D71/10 EN ELEMENTO N. M20 S/CASS.V.G.
COMMERCIAL LINE	DIAMANTE
DIM. WIDTH	200 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	870 mm
NET WEIGHT	16 Kg
VOLUME (net)	0.127
PACKAGE LENGTH	440 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	1160 mm
PACKAGE VOLUME	0,435 m3
GROSS PACKING WEIGHT	25 Kg

NEUTRAL ELEMENT WITH OPEN COMPARTMENT

CODICE
CR0995019

MODELLO
D71/10EN

SERIE
DIAMANTE 70



Modular, easy to combine and robust.



Drawers for GN 1/1



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

NEUTRAL ELEMENT WITH OPEN COMPARTMENT

CODICE
CR0995019

MODELLO
D71/10EN

SERIE
DIAMANTE 70

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
MA97432000	R	WHEEL KIT (2 + 2) Ø 100
MA97433000	RI	WHEEL KIT (2 + 2) Ø 101 STAINLESS STEEL
CR0592869	PZM	NO. 4 STAINLESS STEEL FEET FOR INSTALLATION ON CONCRETE PLINTH
CR0593580	9PT	No. 4 stainless steel feet for installation on tops
CR0592879	KPA	N.2 STAINLESS STEEL FEET WITH FLANGE
CR0592940	9CAT*	Water column for top equipment
CR0599859	7CAM*	Water dispensing column for equipment on oven, open compartment or monoblock