

REFRIGERATED CABINET - TEMP. -2/+8 °C - 1 DOOR - 475 LT

CODICE
OHSTNN

MODELLO
OHSTNN

SERIE
REFRIGERATED
CABINETS



GENERAL CHARACTERISTICS

The main advantage of good refrigeration is to store food safely and hygienically, reducing the risk of contamination and spoilage. With their stainless steel capacity and structure, the refrigeration equipment ensures optimal preservation of vegetables, meat, fish, ice cream and creams, while maintaining their flavour and fragrance. Compliance with hygiene and food safety standards, reduced energy costs and increased efficiency in kitchen work are aspects that guided OLIS in the development of a new range of refrigeration equipment.

One-piece construction with AISI304 stainless steel interior and exterior finish. Dashboard openable for easy periodic maintenance (condenser cleaning). Inner compartment moulded sides, 3 Rilsan GN2/1 grids included. External back and sternum base in pre-painted steel. Magnetic gasket on all four sides and counter-magnet on the gasket rebates. Ergonomic full-height handle recessed into the front of the door for easy opening in any type of installation. Indirect ventilation thanks to the full-height ducting system for optimal air circulation and uniform temperature distribution. Environmentally friendly refrigerant R290

TECHNICAL SPECIFICATIONS

- Stainless steel interior and exterior.
- 75 mm wall insulation with CFC-free polyurethane.
- Dashboard can be opened to facilitate periodic maintenance (condenser cleaning).
- Cell interior with radiused corners for easy cleaning.
- 150 mm steel feet adjustable in height.
- Automatic defrosting with dissipation of condensation water by hot gas.

- Doors with self-closing hinges.
- Standard lock.
- Provision for positioning on plinth.
- Buffered monoblock, outside the cell, with forced ventilation from top to bottom.
- Digital control with Touch EV3 alarm and error indications.

REFRIGERATED CABINET - TEMP. -2/+8 °C - 1 DOOR - 475 LT

CODICE
OHSTNN

MODELLO
OHSTNN

SERIE
REFRIGERATED
CABINETS

Technical Information

SPECIFICATION	DATA
MATERIAL	OHSTNN
SUPPLY	ELECTRICS
DIM. WIDTH	700 mm
DIM. PRODUCTIVITY	700 mm
DIM. HEIGHT	2080 mm
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50 HZ
ELECTRICAL POWER	0.28 kW
ENERGY CLASS	B
CELL SIZE	550X 580X 1480

REFRIGERATED CABINET - TEMP. -2/+8 °C - 1 DOOR - 475 LT

CODICE
OHSTNN

MODELLO
OHSTNN

SERIE
REFRIGERATED
CABINETS



The temperature is constantly adjusted and controlled through the simple and intuitive Digital Display.



Key lock provided as standard.



Molded cell bottom with rounded edges and removable grid supports for maximum hygiene and loading flexibility.