

# REFRIGERATED CABINET - TEMP. -25°-15° - 700 LT -25-15°C 1 DOOR - TOUCH CONTROL - GAS R290

CODICE  
BN20SC02OM35T4W

MODELLO  
OFT70BT-T4W

SERIE  
REFRIGERATED  
CABINETS



## GENERAL CHARACTERISTICS

The main advantage of good refrigeration is to store food safely and hygienically, reducing the risk of contamination and spoilage. With their stainless steel capacity and structure, the refrigeration equipment ensures optimal preservation of vegetables, meat, fish, ice cream and creams, while maintaining their flavour and fragrance. Compliance with hygiene and food safety standards, reduced energy costs and increased efficiency in kitchen work are aspects that guided OLIS in the development of a new range of refrigeration equipment.

One-piece construction with AISI304 stainless steel interior and exterior finish. Dashboard openable for easy periodic maintenance (condenser cleaning). Inner compartment moulded sides, 3 Rilsan GN2/1 grids included. External back and sternum base in pre-painted steel. Magnetic gasket on all four sides and counter-magnet on the gasket rebates. Ergonomic full-height handle recessed into the front of the door for easy opening in any type of installation. Indirect ventilation thanks to the full-height ducting system for optimal air circulation and uniform temperature distribution. Environmentally friendly refrigerant R290

## TECHNICAL SPECIFICATIONS

■ Internal and external in stainless steel. Sides stamped (excluding models 35/35 and 70/70). Wall insulation of 83 mm with CFC-free polyurethane. Dashboard openable for easy periodic maintenance (condenser cleaning). Touch screen control. Cell interior with rounded corners for easy cleaning. 150 mm adjustable steel feet. Automatic defrost with resistance and condensate water dissipation through hot gas. Self-closing doors with hinges. Standard lighting and lock for cell

illumination. Prepared for placement on plinth. Buffer monoblock, external to the cell, with forced ventilation from top to bottom. ■ Frost-T Versions Exclusive advanced and intuitive Touch Control. At a glance, you can check all operating parameters and modify them with a few simple touches.

REFRIGERATED CABINET - TEMP. -25°-15° - 700 LT  
-25-15°C 1 DOOR - TOUCH CONTROL - GAS R290

CODICE  
BN20SC02OM35T4W

MODELLO  
OFT70BT-T4W

SERIE  
REFRIGERATED  
CABINETS

### Technical Information

SPECIFICATION	DATA
MATERIAL	BN20SC02OM35T4W
DIM. WIDTH	700 mm
DIM. PRODUCTIVITY	830 mm
DIM. HEIGHT	2080 mm
NET WEIGHT	124 Kg
PACKAGE LENGTH	860 mm
PACKAGE WIDTH	760 mm
PACKAGING HEIGHT	2220 mm
PACKAGE VOLUME	1.45 m3
GROSS PACKING WEIGHT	139 Kg
STANDARD POWER SUPPLY	220-240V 1N
ELECTRICAL POWER	0.54 kW
GAS/REFRIGERANT TYPE	R290
REFRIGERATION POWER	664
CELL SIZE	550X710X1480 MM
RATED CURRENT	2.6
Capacity	562 LT

# REFRIGERATED CABINET - TEMP. -25°-15° - 700 LT -25-15°C 1 DOOR - TOUCH CONTROL - GAS R290

CODICE  
BN20SC02OM35T4W

MODELLO  
OFT70BT-T4W

SERIE  
REFRIGERATED  
CABINETS

