

COMBINED ELECTRIC DIRECT STEAM OVEN - 7 X 1/1 GN - ELECTRONIC CONTROL

CODICE
MEET071E

MODELLO
MEET071E

SERIE
MEMOLIS PRO



GENERAL CHARACTERISTICS

Olis ovens ideal for you who are opening a bar, restaurant or bakery. You have the opportunity to have all the features and performance of top-of-the-line ovens with Olis' signature quality. With a simple and intuitive control system, you can unleash your creativity in the kitchen. Every dish a masterpiece: from steaming to frying to grilling; bring to the table whatever the imagination suggests, from sweet to savory.

Memolis Pro - Professional oven for catering.

Perfectly smooth and airtight baking chamber with rounded edges.

Closing door with double tempered, air gap glass and heat-reflective inner glass for less heat radiation to the operator and greater efficiency.

Inner glass with folding opening for easy cleaning operation.

Opening baffle for easy cleaning operation of the fan on open cabinet.

Adjustable door hinges for optimal sealing.

COMBINED ELECTRIC DIRECT STEAM OVEN - 7 X 1/1 GN - ELECTRONIC CONTROL



weinnovate cooking

CODICE
MEET071E

MODELLO
MEET071E

SERIE
MEMOLIS PRO

TECHNICAL SPECIFICATIONS

■ The Touch oven control panel has high-visibility LED alphanumeric displays (HVS - High Visibility System) to ensure clear readability. It also features a 2.4-inch color display (LCD - TFT) that allows you to view your favorite programs, preset programs, variable fan options, automatic washing, menu and settings in a clear and intuitive manner.

■ **COOKING MODE:** Automatic with 95 tested and memorised cooking programmes, including programmes for reheating on plate and baking tray. Programmable with the possibility of storing 99 cooking programmes in automatic sequence (up to 9 cycles) by assigning a dedicated name and icon. Manual cooking with three cooking modes with immediate start: convection from 30°C to 260°C, steam from 30°C to 130°C, combined convection + steam from 30°C to 260°C. **Clima®** - Automatic system for measuring and controlling the percentage of humidity in the cooking chamber. Quick scroll & push selection of favourite programmes, with dedicated scroller.

OPERATION: HVS (High Visibility System) alphanumeric LED displays for temperature, Clima, time and core temperature. 2.4 inch colour display (LCD - TFT) for displaying favourite programmes, preset programmes, ventilation, automatic washing, menus, settings. **SCROLLER** knobs with Scroll and Push function to confirm choices. Manual preheating.

CONTROL FEATURES: Autoreverse (automatic reversal of fan rotation direction) for perfect cooking uniformity. Automatic chamber vent control. Manual humidifier. LED cooking chamber lighting. Easy

access to programmable user parameters, to customise the appliance via user menus. 2 ventilation speeds, the reduced speed activates the reduction of heating power. Intermittent speed is available for special cooking. Core temperature control with 4-point probe (core probe optional). Needle core probe ø 1 mm, for vacuum cooking and small pieces (optional). USB connection for downloading HACCP data, updating software and uploading/downloading cooking programs. Preparation for SN energy optimisation system (optional). **SERVICE** programme: Electronic board function test - Temperature probe display - Equipment operating hours counter for all main functions for scheduled maintenance. Functional check self-diagnosis before starting to use the equipment, with descriptive and acoustic signalling of any anomalies. **EcoSpeed** - Based on the quantity and type of product, the oven optimises and controls the energy supply, always maintaining the right cooking temperature and avoiding fluctuations. **EcoVapor** - The EcoVapor system achieves a clear reduction in water and energy consumption by automatically controlling the steam saturation in the cooking chamber. IPX3 protection against water jets.

MAINTENANCE CLEANING: LCS (Liquid Clean System) automatic cleaning system (optional), with integrated tank and automatic dosage (CombiClean liquid detergent, in 100% recyclable cartridges. Supplied with 1 cartridge canister of liquid detergent CDL05 - 990 g). 7 automatic washing programmes. Manual washing system with external hand shower (hand shower optional).



Sistema Qualità Certificato ISO 9001

Olis Ali Group S.r.l.

Via Del Boscon, 424 - 32100 Belluno - Italy

Web: olis.it - Mail: info@olis.it

18/4/2024 Pag. 2/6

COMBINED ELECTRIC DIRECT STEAM OVEN - 7 X 1/1 GN - ELECTRONIC CONTROL

CODICE
MEET071E

MODELLO
MEET071E

SERIE
MEMOLIS PRO

Technical Information


| SPECIFICATION | DATA |
|------------------------------|------------------------------|
| MATERIAL | MEET071E |
| DEFINITION | ICET071E MISTO EL.7T C/TOUCH |
| COMMERCIAL LINE | ICON E |
| SUPPLY | ELECTRICS |
| DIM. WIDTH | 812 mm |
| DIM. PRODUCTIVITY | 725 mm |
| DIM. HEIGHT | 935 mm |
| NET WEIGHT | 95 Kg |
| VOLUME (net) | 0.55 |
| PACKAGE LENGTH | 910 mm |
| PACKAGE WIDTH | 870 mm |
| PACKAGING HEIGHT | 1160 mm |
| PACKAGE VOLUME | 0,918 m3 |
| GROSS PACKING WEIGHT | 109 Kg |
| STANDARD POWER SUPPLY | 3NAC400V/3AC230V 50Hz |
| ELECTRICAL POWER | 12.5 kW |
| GAS/REFRIGERANT TYPE | NO GAS |
| IP GRADE | IPX3 |
| CERTIFIED MODEL | MEET071E |

COMBINED ELECTRIC DIRECT STEAM OVEN - 7 X 1/1 GN - ELECTRONIC CONTROL

CODICE
MEET071E

MODELLO
MEET071E

SERIE
MEMOLIS PRO



Dimensions: Millimeters [inches]

ICET071E/ICEM071E

I dati riportati sul presente documento sono da ritenersi non vincolanti. L'azienda si riserva di apportare modifiche tecniche in qualsiasi momento.
The specification shown in this document are to be considered non binding. The company reserves the right to make technical change at any moment.
Die auf dieser Unterlage angegebenen technischen Daten sind als unverbindlich anzusehen. Die Firma behält sich das Recht vor zu jeder Zeit technische Änderungen vorzunehmen.
Les données techniques sur ce document ne doivent pas être considérées contraignantes. La société se réserve le droit d'apporter des modifications techniques à tout moment.
Los datos técnicos indicados en el presente catálogo no son vinculantes. La empresa se reserva el derecho de efectuar modificaciones sin previo aviso.

COMBINED ELECTRIC DIRECT STEAM OVEN - 7 X 1/1 GN - ELECTRONIC CONTROL

CODICE
MEET071E

MODELLO
MEET071E

SERIE
MEMOLIS PRO

OPTIONAL

| MODELLO | DESCRIZIONE |
|--|---|
|  NPK | PREARRANGEMENT FOR SUCTION HOOD CONNECTION |
| ISP664 | SUPPLEMENT FOR BAKERY VERSION IGP-664 TRAY HOLDER BULKHEAD |
| ISC04 | MULTIPOINT CORE PROBE. Ø 3 MM - T VERSION |
|  ISA01 | NEEDLE CORE PROBE. Ø 1 MM - T VERSION |
| IPS071 | OPPOSITE DOOR |
|  ILCS2 | LCS AUTOMATIC WASHING SYSTEM - 1 CARTRIDGE CANISTER OF LIQUID DETERGENT INCLUDED CDL05 - 990 GR. - T VERSION" |
|  SN | ENERGY OPTIMIZATION SUPPLEMENT. FOR ELECTRIC MODELS ONLY |
|  APDS | SECURITY DOOR OPENING WITH DOUBLE CLICK |
|  TS-ICE-071E-F60 | 3-AC 480 V - 60 HZ |
|  TS-ICE-071E-F50 | 3-AC 480 V - 50 HZ |
|  TS-ICE-071E-E60 | 3N-AC 440 V - 60 HZ |
|  TS-ICE-071E-E50 | 3N-AC 440 V - 50 HZ |
|  TS-ICE-071E-D60 | 3-AC 440 V - 60 HZ |
|  TS-ICE-071E-D50 | 3-AC 440 V - 50 HZ |
|  TS-ICE-071E-C60 | 3-AC 400 V - 60 HZ |
|  TS-ICE-071E-C50 | 3-AC 400 V - 50 HZ |

COMBINED ELECTRIC DIRECT STEAM OVEN - 7 X 1/1 GN - ELECTRONIC CONTROL

CODICE
MEET071E

MODELLO
MEET071E

SERIE
MEMOLIS PRO

ACCESSORIES

| CODE | MODELLO | DESCRIZIONE |
|----------|----------|--|
| IKKV51S | IKKV51S | EXTRACTION HOOD WITH AIR-COOLED CONDENSER FOR STACKING KIT. PREARRANGED ELECTRIC MODELS ONLY |
| RP04 | RP04 | SET OF CASTORS FOR STANDS, 2 OF WHICH WITH BRAKES |
| NPT071 | NPT071 | TRAY HOLDER - INSERTABLE ON 45 MM CENTRE DISTANCE SUPPORT |
| NPT064 | NPT064 | TRAY HOLDER - INSERTABLE ON STAND |
| NPF04 | NPF04 | FLANGED FEET KIT FOR SUPPORTS, FOR NAVAL INSTALLATIONS |
| KISC04 | KISC04 | MULTIPOINT CORE PROBE KIT. Ø 3 MM - T VERSION |
| KISA01 | KISA01 | CORE NEEDLE PROBE KIT. Ø 1 MM - VERSION T |
| KIPS071E | KIPS071E | KIT FOR OPPOSITE HINGED DOOR |
| KFP002 | KFP002 | FOOT STOPPER KIT |
| ISR071S | ISR071S | STAINLESS STEEL BASE SUPPORT FOR BLAST CHILLER INSERTION MOD. 050-051 - FULL AISI 304 |
| ISR071E | ISR071E | STAINLESS STEEL BASE SUPPORT - FULL AISI 304 |
| ILV126 | ILV126 | PROVING CABINET WITH HUMIDIFIER AND PROGRAMMABLE DIGITAL CONTROLS - GLASS DOORS |
| IKKV51 | IKKV51 | FUME HOOD WITH AIR CONDENSER |
| IGP716 | IGP716 | PAIR OF SHELF RACKS - GN - 600 X 400 |
| IGP664 | IGP664 | PAIR OF BULKHEADS - 600 X 400 |
| ICLD | ICLD | HAND SHOWER COMPLETE WITH FITTINGS AND CONNECTIONS |
| ICFX02 | ICFX02 | FAT FILTER - 2pcs |
| IBAS051 | IBAS051 | SHATTERPROOF BAR |
| PCSM | PCSM | FLOWMETER 10-100 |
| PCSK | PCSK | PURITY C STEAM FILTER HEAD KIT |
| PCSF | PCSF | PURITY C STEAM 1100 CARTRIDGE |
| CCE | CCE | HOOD MANIFOLD FOR EXTERNAL CONNECTION - Ø 150 MM |
| PLG5032 | PLG5032 | PLUG - 380 V - 32A - 5P |
| CBL5025 | CBL5025 | CABLE - 3 MT - 5 X 2,5 MMQ |
| RP004 | RP004 | WHEEL SET OF WHICH 2 WITH BRAKE |
| IKG071 | IKG071 | STACKING KIT |
| IKG051 | IKG051 | STACKING KIT |
| IKE071 | IKE071 | STACKING KIT |
| IKE051 | IKE051 | STACKING KIT |