

HIGH TECH WASH PLUS - OPHTW2SPLUS

CODICE
BND211089

MODELLO
OPHTW2SPLUS

SERIE
WASHING



GENERAL CHARACTERISTICS

Professional dishwashers designed to meet the needs for efficient and rapid cleaning of dishes and utensils in commercial settings, such as restaurants, hotels, and similar food facilities. Olis equipment is designed to handle a high volume of tableware and ensure high hygiene standards in commercial settings.

TECHNICAL SPECIFICATIONS

■ The new technology of potwashers allows you to easily and intuitively follow all the stages of your potwashing process directly from the control panel. The innovative rinsing circuit, the energy saving function (a device that optimises energy functions avoiding unnecessary waste) the high level of performance and the high quality materials make these machines extremely competitive and versatile.

■ Optional heat recovery unit (TR) ■ Electronics with energy-saving function ■ Double wall ■ Standard rinse pump ■ Totally moulded step basin ■ Independent stainless steel wash/rinse arms ■ Split sump filter with removable sump + pump filter ■ Thermostop to ensure rinsing temperature in accordance with HACCP requirements ■ Automatic machine cleaning cycle

HIGH TECH WASH PLUS - OPHTW2SPLUS

CODICE
BND211089

MODELLO
OPHTW2SPLUS

SERIE
WASHING

Technical Information


SPECIFICATION	DATA
MATERIAL	BND211089
DEFINITION	OPHTW2SPLUS LAVAOGGETTI EL. 70X70
DIM. WIDTH	840 mm
DIM. PRODUCTIVITY	885 mm
DIM. HEIGHT	1790 mm
NET WEIGHT	203 Kg
VOLUME (net)	1,331
PACKAGE LENGTH	940 mm
PACKAGE WIDTH	900 mm
PACKAGING HEIGHT	1940 mm
PACKAGE VOLUME	1,641 m3
GROSS PACKING WEIGHT	227 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50Hz
ELECTRICAL POWER	12.5 kW
CERTIFICATE NR	3/6/9/12 min
WASH PUMP	1750W
CERTIFICATE NR	12500W
WATER CONSUMPTION	4,3 lt

HIGH TECH WASH PLUS - OPHTW2SPLUS

CODICE
BND211089

MODELLO
OPHTW2SPLUS

SERIE
WASHING



Stabilized pressure rinsing and constant boiler water temperature of 85°C. Thanks to the atmospheric boiler, mixing of mains water in the rinse phase is avoided. The PLUS system also ensures greater control and correct dosing of rinse aid in each cycle.



Fully molded basin. Independent stainless steel wash/rinse arms



Double-walled door