

GAS SOLID TOP WITH TWO BURNERS ON THE LEFT - TOP VERSION

CODICE
CR0995529

MODELLO
D96/10TCTGSX

SERIE
DIAMANTE 90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

■ Cast iron centre plate and ring. ■ Steel burner controlled by thermocouple safety valve. ■ Piezoelectric ignition with liquid-protected push button. ■ Adjustable temperature on the plate from 50° to 450°C. ■ Thermocouple safety valves with pilot flame.

■ Thick top plate with removable centre ring. ■ A single high-efficiency central burner that results in differentiated heat zones on the floor with a concentration of maximum heat in the centre and decreasing temperatures in the peripheral zones. ■ Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

GAS SOLID TOP WITH TWO BURNERS ON THE LEFT - TOP VERSION

CODICE
CR0995529

MODELLO
D96/10TCTGSX

SERIE
DIAMANTE 90

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0995529
DEFINITION	D96/10 TCTGSX TUTTAPIAST.G.2 F SX TOP
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	1200 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	250 mm
NET WEIGHT	155 Kg
VOLUME (net)	0.27
PACKAGE LENGTH	0 mm
PACKAGE WIDTH	0 mm
PACKAGING HEIGHT	0 mm
PACKAGE VOLUME	0,600 m3
GROSS PACKING WEIGHT	166 Kg
GAS POWER	24,50
GAS POWER (G25.3/25mbar)	22,50
CERTIFIED MODEL	D96/10 TCTGSX

GAS SOLID TOP WITH TWO BURNERS ON THE LEFT - TOP VERSION


CODICE
CR0995529

MODELLO
D96/10TCTGSX

SERIE
DIAMANTE 90

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRTNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm
MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda


- E** Pressacavo entrata linea elettrica - Stopfbuchse
Electric cable stress relief - Presse étoupe de câble él
Pisacable - Elektrische kabelwartel
- G** Attacco arrivo gas - Gasanschluss - Gas connection
Arrivée gaz - Union de gas - Gasaansluiting
EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
- H2O*** Attacco arrivo acqua - Wasseranschluss - Water inlet
Arrivée eau - Union de agua - Wateraansluiting
EN ISO 228-1 G 3/4

GAS SOLID TOP WITH TWO BURNERS ON THE LEFT - TOP VERSION

CODICE
CR0995529

MODELLO
D96/10TCTGSX

SERIE
DIAMANTE 90



Thick top plate with removable centre ring.



A single high-efficiency central burner that results in differentiated heat zones on the floor with a concentration of maximum heat in the centre and decreasing temperatures in the peripheral zones.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

GAS SOLID TOP WITH TWO BURNERS ON THE LEFT - TOP VERSION

CODICE
CR0995529

MODELLO
D96/10TCTGSX

SERIE
DIAMANTE 90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1353839	CR1353839	Smooth cast iron radiant plate 39.4x34.8 cm
CR1353849	CR1353849	Striped radiant plate 39.6x34.8 cm
CR1355489	D96/10B	Open base 120cm series 90
CR0996979	DBVP4	Diamond door 39.5x3.6x46.5 cm for 40 cm compartments
CR0997009	DBVPA4	Accessory Diamond door 39.5x3.6x46.5 cm for 40 cm compartments
CR0997029	DAPC	Accessories for accessory diamond knife holder
CR0997019	DAPD	Accessories for Diamond door accessories
CR0997039	DAPS	Accessories for diamond spice rack
CR0997049	DAPM	Accessories for accessory Diamond door
CR0997059	DAPDB	Accessories for accessory Diamond door/bottle holders
CR1353589	DBVC4	Drawer kit 39.5x56x46.5 cm for compartments of 40